

AP904 Whole of house filtration system



Cleaner Clearer Better Tasting Water







Sanitary Quick Change (SQC)

Helps provide easier and cleaner cartridge change-out



WaterMark Certified

Industry tested and proven to ensure consistent trust and peace of mind



Better Quality Water

Up to 85% chlorine taste and odour reduction using patented carbon block technology




Appliance Protection

Helps extend the life of water-using appliances such as water heaters, dishwashers and clothes washers









WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. If system is not used for 2 days or more, flush 5-10 litres of water through before consuming water.

AP904 Whole of house filtration system

Product Benefits

Convenience

- Sanitary Quick Change (SQC) helps provide easier and cleaner cartridge change-out
- Helps extend the life of water-using appliances such as water heaters, dishwashers and clothes washers

Better quality water

- Quality drinking water
- · Reduces impurities that may be present in mains water
- Up to 85% chlorine taste and odour reduction using patented carbon block technology
- WaterMark certified to Australian Standards for your peace of mind and protection

Capacity

• 378,000 litres (up to 12 months)

Health & well being

Perfect for a healthy lifestyle

Features

- 1" BSP male outlet / inlet connections with a 1" centre core help provide high-flow ratings
- 37.8 lpm flow rate meet the demands of most homes and small businesses
- 378,000 litres or one-year cartridge life under most water quality conditions
- Die-cast zinc locking latch helps prevent the possibility of the cartridge backing out based on varying water pressures or surges
- Sanitary Quick Change (SQC) cartridge change-out with self-venting action helps eliminate the need for wrenches and pressure relief valves, and minimises water spillage as compared to industry-standard drop-in housings
- NSF Std 42 listed for materials and structural conformances

Replacement Cartridge: AP917HD-S

- Reduces sediment* & chlorine*, improves taste & odour* and protects equipment from scale*
- Nominal micron rating: 5 μm
- Capacity: 378,000 litres*
- Flow rate: 37.8 lpm*
- Temperature: 4.4-38 °C
- Pressure: 172-862 kPa



^{*} Tested in accordance to manufacturer's internal laboratory standard.