



Glass table (sold separately)
COMP720

COMP710-3	
Bromic Part no	COMP710-3
Colour	Stainless steel
Cylinder housing	Flat top
Maximum Output (Mj/hr)	50
Heats approx. m ²	25
Cylinder compatibility	15kg or 9kg
Height (mm)	2220
Reflector diameter (mm)	813
Fixed Wheels	Yes



COMMERCIAL GRADE

COMP710-3 Patio Heater

- Curved stainless steel control panel
- Heats approximately 25m²
- New direct ignition piezo for easy lighting
- Durable wheels
- Stainless steel burner ensures maximum heater life
- Single piece 813mm diameter reflector
- Includes protective cover
- AGA approved

HEATFLO



2 Tile
16Mj. heat output



3 Tile
25Mj. heat output



5 Tile
45Mj. heat output

- Outdoor and non-residential indoor use*
 - Manual Piezo ignition
 - Flame safeguard system to ensure safety
 - Includes wall-mounting bracket
 - Designed for commercial applications* eg. restaurants, warehouses, and factories.
 - AGA approved
- Accessories: (sold separately)
- Moveable trolley & stand suits 9kg and 45kg cylinders
 - Heat Shield

**Must be installed by an authorised person only*



Trolley and Stand
Part no. 2620160
(Cylinder not included)
(Not for use with 5 Tile)

	2 Tile	3 Tile	5 Tile
Bromic Part no. LPG	2620110	2620100	2620120
Bromic Part no. Natural Gas	2620111	2620101	2620121
Gas consumption per 45kg	135 hours approx.	90 hours approx.	50 hours approx.
Height (mm)	334	334	334
Depth (mm)	180	180	180
Width (mm)	387	499	695
Weight (kg)	3.9	5.8	7.1
Heat Output on LPG (Mj)(BTU)	16Mj (17,000 BTU)	25Mj (25,300 BTU)	45Mj (42,000 BTU)
Ceiling clearance reqd. (m)	1.2	1.2	1.2
Approx. area heated in m ²	12m ²	16m ²	25m ²
Stand dimensions (mm)	480w x 430d x 1200h		